



Valve Size	Valve			Double-Acting Actuator				Spring-Return Actuator			
	D	H	L	MODEL	A	B	G	MODEL	A	B	G
1/4	0.39	1.28	2.64	52D	5.49	2.80	3.52	52S	5.49	2.80	3.52
3/8	0.39	1.28	2.64	52D	5.49	2.80	3.52	52S	5.49	2.80	3.52
1/2	0.56	1.28	2.64	52D	5.49	2.80	3.52	52S	5.49	2.80	3.52
3/4	0.75	1.36	3.00	52D	5.49	2.80	3.52	52S	5.49	2.80	3.52
1	0.95	1.79	3.35	52D	5.49	2.80	3.52	52S	5.49	2.80	3.52
1-1/4	1.18	1.93	3.66	52D	5.49	2.80	3.52	52S	5.49	2.80	3.52
1-1/2	1.49	2.52	4.13	52D	5.49	2.80	3.52	75S	8.15	3.72	4.61
2	1.97	2.88	4.80	52D	5.49	2.80	3.52	75S	8.15	3.72	4.61
2-1/2	2.52	3.48	6.10	63D	6.37	3.20	3.96	85S	9.35	4.17	5.06
3	3.00	3.85	6.89	63D	6.37	3.20	3.96	85S	9.35	4.17	5.06
4	3.74	4.59	8.03	100D	10.69	4.84	5.57	125S	14.41	5.83	7.22

FNW™		4120 NE Columbia Blvd Portland, OR 97211 Phone (503) 287-8383 Fax (503) 281-9677	
		TITLE/DESCRIPTION: FIGURE 440 BV WRPA DIRECT MOUNT	
DATE: 7-18-05	BY: PEA	UNITS: INCHES	
SCALE: NONE	APP'D:	PAGE(S): 1	
MODEL: 440/ACT			
DWG NO: DM440P			
NOTES:			
FILE: DM440Pneu	WT:	LOC: PORTLAND	
PAGE SIZE: 8.5 x 11L	REV: 0	R'DATE:	
THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF FNW VALVE AND IS SUBMITTED TO YOU FOR THE LIMITED PURPOSE OF PROVIDING YOU INFORMATION ON PRODUCTS AND SYSTEMS PURCHASED FROM FNW VALVE. BY RECEIVING THIS DOCUMENT, YOU AGREE NOT TO DISCLOSE SUCH INFORMATION TO OTHERS EXCEPT BY WRITTEN PERMISSION OF FNW VALVE.			