3 PC FULL PORT 1000 CWP w/ ISO MOUNTING PAD

Features:

- 1000 PSI CWP Non-Shock
- 150 PSI WSP
- Full Port
- Blow-out Proof Stem
- Live-Loaded Packing
- Anti-static Design
- Investment Cast Body
- RTFE Seats
- End Connections
  - Threaded
  - Socket Weld
- 4" With Handle Standard (Lock-out Style)
- Direct Mounting Pad
- Vacuum rated to 26.967"Hg (75 Torr)*
- Vented Ball
- Manufactured Silicone Free

Standards:

- Design: ASME B16.34, MSS SP-110
- End Connections:
  - NPT - ASME B1.20.1
  - SW - ASME B16.11
- Mounting Pad: ISO 5211
- Seat/Shell Test: MSS SP-110

* Vacuum measurements are often made in inches of mercury below atmospheric pressure. The values calculated here assume standard atmospheric pressure of 29.92 inches of mercury.





4" with Handle - Standard

Cv, Torque & Weight

Size	Cv	Torque (in-lbs)	Wt (lbs)
1/4	15	60	1.01
3/8	15	60	1.03
1/2	18	66	1.05
3/4	36	80	1.73
1	48	146	2.33
1-1/4	58	242	4.30
1-1/2	120	344	5.21
2	190	503	9.09
2-1/2	450	631	17.31
3	600	1337	24.36
4	1100	1959	51.00

Figure Number Matrix

FNW 310AM Ends Size

END CODE		SIZE CODE	
Blank = Threaded NPT	1/4 = B	1 = G	2-1/2 = L
SW = Socket Weld	3/8 = C	1-1/4 = H	3 = M
	1/2 = D	1-1/2 = J	4 = P
	3/4 = F	2 = K	

Figure 310AM
STAINLESS STEEL BALL VALVES

3 PC FULL PORT 1000 CWP





Bod Bolts
Sizes 1/4"~2 1/2"



Body Bolts
Sizes 3" & 4"





ISO Pad
Sizes 1-1/2"~3"



ISO Pad
Size 4"



Handle Assembly
Size 4"



Socket Weld Ends

Standard Materials

Ref. No.	Description		Material	Qty
1	Body		ASTM A351 Gr. CF8M Stainless	1
2	End Cap	NPT	ASTM A351 Gr. CF8M Stainless	2
		SW	ASTM A351 Gr. CF3M Stainless	
3	Ball		316SS Stainless	1
4	Seat		RTFE	2
5	Body Gasket		PTFE	2
6	Stem		316SS Stainless	1
7	Anti-Static Device		316SS Stainless	2
8	Thrust Washer		PTFE	1
9	O-Ring		FKM	1
10	V-Ring Packing		PTFE	1 Set
11	Bushing		50% Stainless + 50% PTFE	1
12	Gland		316SS Stainless	1
13	Belleville Washer		301SS Stainless	2
14	Stem Nut		ASTM A194-8 Stainless	1
15	Stop-Lock-Cap		304SS Stainless	1
16	Bolt Washer	1/4"~2"	304SS Stainless	4
		2-1/2"		8
		3"~4"		12
17	Bolt Nut	1/4"~2"	ASTM A194-8 Stainless	4
		2-1/2"		8
		3"~4"		12
18	Body Bolt	1/4"~3"	ASTM A193-B8 Stainless	4
		4"		6
19	Handle Adapter 4"		ASTM A351 Gr. CF8 Stainless	1
20	Pipe Handle 4"		ASTM A53 Steel + Zinc Plating	1
21	Set Screw 4"		ASTM A193-B8 Stainless	1
22	Triangle Stopper 4"		420SS Stainless	1
23	Handle Sleeve 4"		Vinyl Plastic	1

Dimensions (inches)

SIZE	Ød	L	Lm	H	P	A	ØE1	ØE2	U1	U2	K (UNF)	Ls	L2	M (UNC)	B	L1	ØB1
1/4	0.42	2.95	1.30	1.65	0.35	0.35	1.42	1.65	0.24	0.24	7/16-20	2.23	1.71	1/4-20	1.10	0.39	0.56
3/8	0.50	2.95	1.30	1.65	0.35	0.35	1.42	1.65	0.24	0.24	7/16-20	2.23	1.71	1/4-20	1.10	0.39	0.70
1/2	0.59	2.95	1.30	1.65	0.35	0.35	1.42	1.65	0.24	0.24	7/16-20	2.23	1.71	1/4-20	1.10	0.39	0.86
3/4	0.79	3.15	1.52	1.91	0.35	0.35	1.42	1.97	0.24	0.28	7/16-20	2.44	1.82	5/16-18	1.36	0.51	1.07
1	0.98	3.54	1.76	2.30	0.43	0.43	1.65	1.97	0.24	0.28	9/16-18	2.79	2.10	5/16-18	1.65	0.51	1.34
1-1/4	1.26	4.33	2.13	2.48	0.43	0.43	1.65	2.76	0.24	0.35	9/16-18	3.37	2.68	3/8-16	2.05	0.63	1.69
1-1/2	1.50	4.72	2.42	2.81	0.55	0.55	1.97	2.76	0.28	0.35	3/4-16	3.81	3.05	3/8-16	2.30	0.63	1.93
2	1.97	5.51	2.95	3.08	0.55	0.55	1.97	2.76	0.28	0.35	3/4-16	4.36	3.59	3/8-16	2.81	0.67	2.42
2-1/2	2.50	7.28	3.62	3.94	0.67	0.67	2.76	4.02	0.35	0.43	7/8-14	5.75	4.36	9/16-12	3.41	0.67	2.91
3	2.99	8.07	2.93	4.27	0.67	0.67	2.76	4.02	0.35	0.43	7/8-14	6.34	4.93	9/16-12	3.98	0.67	3.54
4	3.95	9.45	3.76	5.51	0.87	0.87		4.02		0.43	1-1/8-12	7.87	6.26	5/8-11	5.20	0.79	4.53

DOC: FNW310AM11 Ver. 01/2011

© 2011 - FNW. All rights reserved.
The FNW logo is a trademark of Ferguson Enterprises, Inc., PL Sourcing, PO Box 2778, Newport News, VA 23609

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice. Always verify that you have the most recent product specifications or other documentation prior to the installation of these products.